



Zintroniconic

Zintroniconic D4

The Zintroniconic D4 dome camera offers a cost-effective solution that provides high quality at an affordable price. Its simplicity goes hand in hand with aesthetics and solid components, which guarantees the user not only an effective, but also a pleasant user experience.

High class and image quality is guaranteed by the GC2083 sensor with a resolution of 4 megapixels and a lens with a focal length of 3.6mm allowing a wide angle of view of 85°. The whole is enclosed in a small dome, ideal for indoor installation. The integrated PoE board allows not only data transfer, but also power supply to the cameras. This allows the camera to be connected to a switch or DVR with a single LAN cable, making installation more convenient and efficient.



4 MEGAPIXELS



OBJECTIVE
3.6 mm



INFRARED
20 M



WATERPROOF
IP66



COMPRESSION
H265



POWER
POE



MOTION
DETECTION



FUNCTION
P2P



PLASTIC
HOUSING



ANDROID,
IOS



SPECIFICATION:

Camera type:	Dome IP PoE
Processor:	FH8852
Sensor:	GC2083
Resolution:	4 MPx - 2560x1440
Frame rate:	25
Lens:	3.6mm (view angle 85°)
Night illumination:	Infrared, distance to 20 metrów
Wired connection:	10/100 Base-T
SD card:	No
NVR compatibility:	VIA ONVIF protocol
Built-in speaker:	No
Built-in microphone:	Yes
Alarm events:	Motion detection, Character detection
Alarm connection:	Saving to e-mail, FTP server
Alarm notifications:	From the application, per email
Reset button:	No
Dedicated app:	BitVision, IVMS320
Housing:	Plastic, IP66
Power supply:	DC 12V/1A, PoE 802.11 af
Dimensions:	φ108x91mm
Weight:	170g
Additional features:	Line crossing, Vehicle detection



zintroniconic.com