



Zintroniconic

Zintroniconic D5

Compact size and high quality image, this is what characterizes the Zintroniconic D5 IP PoE camera. Excellent images are guaranteed by the branded 1/2.8" SONY Starvis Back-illuminated CMOS sensor with a resolution of 5 megapixels and a 2.8mm lens allowing a wide viewing angle of 109°. All components are enclosed in a small metal housing, measuring only 93mm in diameter and guaranteeing IP67 rating.

The D5 PoE is an excellent choice wherever you want it to be as invisible as possible. The D5 is equipped with modern infrared LEDs that allow monitoring the area at night at a distance of up to 15 meters. Thanks to the use of innovative technologies, the ZINTRONICONIC D5 PoE camera has an IP67-rated housing - which means it can be used outdoors regardless of weather conditions.



5 MEGAPIXELS



OBJECTIVE
2.8 mm



INFRARED
15 M



WATERPROOF
IP67



COMPRESSION
H265



POWER
POE



MOTION
DETECTION



SD CARD
to 512GB



METAL
HOUSING



ANDROID,
IOS



SPECIFICATION:

Camera type:	Dome IP PoE
Processor:	NT98566
Sensor:	Sony IMX335
Resolution:	5 MPx - 2592x1944
Frame rate:	30
Lens:	2.8mm (view angle 109°)
Night illumination:	Infrared, distance to 15 meters
Wired connection:	10/100 Base-T
SD card:	Yes (do 512GB)
NVR compatibility:	via ONVIF protocol
Built-in speaker:	No
Built-in microphone:	Yes
Alarm events:	Motion detection, Character detection
Alarm connection:	Saving to memory card, FTP server, Siren
Alarm notifications:	From the app, to email, Alarm
Reset button:	Next to the memory card slot
Dedicated app:	BitVision, IVMS320
Housing:	Metal, IP67
Power supply:	DC 12V/2A, PoE 802.11 af
Dimensions:	φ93x74
Weight:	410g
Additional features:	Line crossing, Vehicle detection



zintroniconic.com