



Zintron V2 GSM

The Zintron V2 GSM will prove its worth wherever there are significant problems with Internet access. The AK3918EV300 sensor and 4mm lens have been enclosed in a modern, small housing with IP66 protection class. The combination of high quality components, rugged housing and GSM module makes the V2 GSM model a camera for special tasks.

The V2 GSM camera has been equipped with additional LEDs that allow to illuminate the area with white light, the camera lights the LEDs automatically during an alarm event. The camera has a sim card slot and 2 antennas to enhance GSM signal reception. This enables remote access to the camera using GSM 3/4G LTE networks. The V2 GSM camera uses a Nano SIM card slot.



SPECIFICATION:

Camera type:	GSM PTZ IP
Processor:	AK3918
Sensor:	GC2063
Resolution:	2 MPx - 1920x1080
Frame rate:	20
Objective:	4mm (85° viewing angle)
Lens Night illumination:	Infrared/White, distance up to 10 metres
Wired connection:	10/100 Base-T
Wireless connection:	Bracket
GSM module:	3G / 4G LTE
Access point function:	Yes
Memory card:	Yes (up to 128GB)
Horizontal/Vertical panning:	Flip angle 355°/100°
DVR co-operation:	Protocol ONVIF
Speaker:	Yes
Microphone:	Yes
Alarm events:	Motion detection, Character detection
Alarm association:	Save to memory card, FTP server, Siren
Alarm notifications:	From application, to email
Reset button:	On the cable
Dedicated app:	V380 Pro, V380 Windows
Housing:	Plastic, IP66
Power supply:	DC 12V/1A
Dimensions:	155mm x 85mm x 205mm
Weight:	334g
Additional features:	Character tracking



2 MEGAPIXELS



OBJECTIVE
4mm



INFRARED
10 M



WATERPROOF
IP66



COMPRESSION
H265



GSM
MODULE



MOTION
DETECTION



SD CARD
TO 128GB



FUNCTION
PTZ



ANDROID,
iOS

